

Double Disc Overseeder 1430A

The Double Disc Overseeder has two rows of discs to cut grooves 30mm apart in the soil, seed is accurately delivered into the groove before the roller closes the groove to protect seed. With a single hopper & easy seed rate adjustment, the DD range is an obvious choice for operators.



Specifications

SKU	122.140.002
Working width (m)	1.41
Working width (inch)	55.5
Max. Working depth (mm)	30
Max. Working depth (inch)	.19 - 1.18
Max. Working speed (km h)	12
Max. Working speed (mph)	7.5
Weight (kg)	1340
Weight (lbs)	2954
Sowing distance (mm)	30
Sowing distance (inch)	1.18
Hopper capacity (L)	260
Hopper capacity (cu.ft.)	9.18
Number of seeding elements	47
Min. Tractor HP required	40
Min. Lifting capacity 610 mm behind the lifting eyes (kg)	1340
Min. Lifting capacity 24 inch behind the lifting eyes (lbs)	2954
Max. capacity (m ² hr)	16920
Max. capacity (ft ² hr)	182125
Three-point hitch	3-point CAT 1-2
Lubricant	EP2
Limited availability	1

Distributed by:



www.centaur-asiapacific.com
info@centaur-asiapacific.com

*Hong Kong, Macau, Malaysia (Johor).