

## Multi-Seeder 1200

The floating twin spike rollers of the Multi-Seeder follow the contours, saturating the surface with small holes. The seed is then accurately distributed onto the surface before an adjustable brush sweeps the seeds into the holes. The rear roller then passes over to cover the seed for germination.



### Specifications

SKU	124.120.002
Operation	Tractor pulled
Working width (m)	1.2
Working width (inch)	47.2
Max. Working depth (mm)	5 - 20
Max. Working speed (km h)	12
Max. Working speed (mph)	7.5
Weight (kg)	619
Weight (lbs)	1365
Hopper capacity (L)	150
Hopper capacity (cu.ft.)	5.3
Min. Tractor HP required	25
Min. Lifting capacity 610 mm behind the lifting eyes (kg)	910
Min. Lifting capacity 24 inch behind the lifting eyes (lbs)	2006
Min. Pressure (bar)	1 - 2
Min. Pressure (psi)	14.5 - 29
Three-point hitch	CAT 1-2
Dimensions (width mm)	1513
Dimensions (height mm)	935
Dimensions (length mm)	1323
Dimensions (width inch)	59.6
Dimensions (height inch)	36.8
Dimensions (length inch)	52.1
Number of rakes	910

### Distributed by:



[www.centaur-asiapacific.com](http://www.centaur-asiapacific.com)  
[info@centaur-asiapacific.com](mailto:info@centaur-asiapacific.com)

\*Hong Kong, Macau, Malaysia (Johor).