

Speedseed 2000

The Speedseed models are ideal to overseed large areas quickly. The individual conical ring sections create seed pockets in the soil in which seed is accurately delivered, the holes are then closed with the roller; the additional spike rear roller increases the holes to 1918 per m² (2294 yd²).



Specifications

| | |
|---|-----------------|
| SKU | 124.210.006 |
| Working width (m) | 2 |
| Working width (inch) | 78.7 |
| Max. Working depth (mm) | 5 - 20 |
| Max. Working depth (inch) | .19 - .78 |
| Max. Working speed (km h) | 12 |
| Max. Working speed (mph) | 7.5 |
| Weight (kg) | 591 |
| Weight (lbs) | 1300 |
| Sowing distance (mm) | 30 |
| Sowing distance (inch) | 1.18 |
| Hopper capacity (L) | 297 |
| Hopper capacity (cu.ft.) | 10.4 |
| Number of holes single spiked roller (m ²) | 990 |
| Number of holes single spiked roller (sq.yd) | 1184 |
| Min. Tractor HP required | 40 |
| Min. Lifting capacity 610 mm behind the lifting eyes (kg) | 595 |
| Min. Lifting capacity 24 inch behind the lifting eyes (lbs) | 1310 |
| Three-point hitch | 3-point CAT 1-2 |
| Lubricant | EP2 |

Distributed by:



www.centaur-asiapacific.com
info@centaur-asiapacific.com

*Hong Kong, Macau, Malaysia (Johor).