

## Verti-Drain® 7212

The Verti-Drain® 7212 is well suited to lower HP tractors, this very capable model for aeration to a depth of 10" /25cm on the more sensitive turf areas. The 7212 is particularly popular on hard to reach areas due to its overall dimensions while maintaining all the features of larger Verti-Drains.



### Specifications

SKU	7212
Operation	Tractor Mounted
Working width (m)	1.2
Working width (inch)	48
Max. Working depth (mm)	250
Max. Working depth (inch)	10
Working speed at hole spacing 65 mm (km h)	1
Weight (kg)	470
Weight (lbs)	1030
Hole distance with 12 mm tines (mm)	65
Hole distance with 1 2 x 6 inch tines (inch)	2.5
Hole distance with 18 mm tines (mm)	100
Hole distance with 3 4 x 9 inch tines (inch)	4
Hole spacing distance driving direction (mm)	25 - 165
Hole spacing distance driving direction (inch)	1 - 6-1/2
Max. Diameter solid tine (mm)	18 x 250
Max. Diameter solid tine (inch)	3/4 x 10
Max. Diameter hollow tine (mm)	25 x 250
Max. Diameter hollow tine (inch)	1 x 10
Min. Tractor HP required	18
Min. Lifting capacity 610 mm behind the lifting eyes (kg)	570
Min. Lifting capacity 24 inch behind the lifting eyes (lbs)	1250
Max. capacity with spacing 65 mm (m <sup>2</sup> hr)	1200
Max. capacity with spacing 2 1 2 inch (ft <sup>2</sup> hr)	11000
Three-point hitch	3-point CAT 1
Rpm Max.	500
Gearbox oil	80W90 3 liter
Lubricant	EP 2
Dimensions (width mm)	1350
Dimensions (height mm)	800
Dimensions (length mm)	1100
Dimensions (width inch)	44
Dimensions (height inch)	32
Dimensions (length inch)	54
Slip clutch setting	450 NM (3983 lbf-in)

### Distributed by:



[www.centaur-asiapacific.com](http://www.centaur-asiapacific.com)  
[info@centaur-asiapacific.com](mailto:info@centaur-asiapacific.com)

\*Hong Kong, Macau, Malaysia (Johor).