



# ***Sand Star CVT***

## ***Smooth Bunkers At Your Budget***

The Sand Star CVT is the bunker and sand rake of choice for golf course superintendents and grounds directors who want a cost-effective solution to smooth bunkers and fields. Equipped with superior traction and stability, the Sand Star CVT is built to last for years to come.

With over 25 accessories and industrial-grade components, the Sand Star CVT is adaptable to the unique needs of your course or sports field. As the latest addition to Smithco's star lineup of bunker and sand rakes, the Sand Star CVT is one you are going to love adding to your fleet.

### **• MAX PRODUCTIVITY**

Both center and rear implements as well as plow, key switch and other controls are conveniently located in operator position. The operator seat and controls are ergonomically designed for safety and comfort while increasing productivity.

### **• MULTIPLE OPTIONS**

With over 25 accessories and industrial-grade components, the Sand Star CVT is built to withstand the needs of your facility for years to come.

### **• DUAL-PEDAL TRACTION**

The Sand Star CVT's dual traction pedal gives the operator the ability to smoothly transition from forward to reverse making for hands-free operation, allowing the operator the ability to focus on steering and plowing.

### **• INDUSTRIAL GRADE**

The Sand Star CVT features an industrial grade 10 hp (7.46 kw) Vanguard motor powering a robust Dana transaxle with Comet CVT Clutches.

**Exceptional Service and Products Since 1967**  
**smithco.com**

***Smithco***  
**WE TAKE YOUR TURF SERIOUSLY**

# Sand Star CVT

## SPECIFICATIONS

# Smithco

United States | 877.833.7648  
International | +1 610.688.4009

### ENGINE

Type	Briggs & Stratton Type tratton Model 19L237
Rated Horsepower	10 hp (7.35 kw)
Engine Throttle	Foot operated at operator's station
Cooling	Air-cooled
Electrical System	10 amp
Fuel Capacity	3.8 qt (3.6 l), minimum 87 octane

### SPEED & SOUND

Transport	0-12 mph (0-19.3 kph)
Reverse	0-5 mph (0-8 kph)
Sound Level	Ear: 85 dB

### TIRES, BRAKES & STEERING

Service Brakes	Mechanical drum type
Tires	Front 20x10-turf10 tires; Rear 25x10-turf12 tires
Parking Brake	Lever controlled
Steering	Manual chain drive

### TRACTION DRIVE

Traction System	Dana CVT, two wheel drive, forward/reverse drive pedals at operator's station
-----------------	---

### WEIGHTS & DIMENSIONS

Ground Clearance	5.5-7 in (13-18 cm)
Height	50 in (1.3 m)
Width	61 in (1.6 m)
Length	68 in (1.7 m)
Wheelbase	51 in (1.3 m)


Distributed by:



[www.centaur-asiapacific.com](http://www.centaur-asiapacific.com)  
[info@centaur-asiapacific.com](mailto:info@centaur-asiapacific.com)

\*Hong Kong, Macau & Singapore.

revised 3/2024



Learn More Today!