

# WideSpin™ 1550

## Broadcast Topdresser

### Specifications

	TOW-BEHIND		TRUCK-MOUNTED
<b>Model</b>	ENGINE POWERED 1550 Electronic Control (#85820) 1550 Manual Control (#85821)	HYDRAULIC POWERED 1550 Electronic Control (#85824) 1550 Manual Control (#85825)	HYDRAULIC POWERED 1550 Electronic Control (#85822) 1550 Manual Control (#85823)
<b>Engine</b>	14 hp Subaru	n/a	n/a
<b>Operator Control</b>	<b>Electric:</b> 3-position switch; 4 programmable presets; onboard rate calculator; instantaneous belt and spinner speed control <b>Manual:</b> Standard 3-position switch with manual control	<b>Electric:</b> 3-position switch; 4 programmable presets; onboard rate calculator; instantaneous belt and spinner speed control <b>Manual:</b> Standard 3-position switch with manual control	<b>Electric:</b> 3-position switch; 4 programmable presets; onboard rate calculator; instantaneous belt and spinner speed control <b>Manual:</b> Standard 3-position switch with manual control
<b>Empty Weight</b>	1,324 lbs (601 Kg)	1,021 lbs (463 Kg)	710 lbs without mounting kit (322 Kg)
<b>Hopper Capacity</b>	21 ft <sup>3</sup> (0.59 m <sup>3</sup> ) struck level; 25 ft <sup>3</sup> (0.71 m <sup>3</sup> ) heaped		
<b>Hopper Size</b>	80" x 59.1" (2.03 x 1.50 m <sup>3</sup> ) at the top		
<b>Spreading Width</b>	9' up to 40' (2.5 up to 12 m)		
<b>Spread Application</b>	0.45 ft <sup>3</sup> per 1,000 ft <sup>3</sup> up to 12 ft <sup>3</sup> per 1,000 ft <sup>3</sup> using patented WideSpin Technology		
<b>Topdressing Speed</b>	8 MPH (12.8 Km/h)	8 MPH (12.8 Km/h)	5 MPH (8 Km/h)
<b>Transport Speed</b>	8 MPH (12.8 Km/h)	8 MPH (12.8 Km/h)	8 MPH (12.8 Km/h)
<b>Conveyor Belt</b>	18" (0.46 m) wide pebble surface composition with heavy duty polyester cord		
<b>Metering Gate</b>	Manually operated with Light Spread/Heavy Spread Calibrations		
<b>Drive</b>	Engine Powered Hydraulics	Tow Vehicle Powered Hydraulics	Truck Powered Hydraulics
<b>Wheels</b>	4 Ply 26.5 x 14.00 x 12 Turf	4 Ply 26.5 x 14.00 x 12 Turf	n/a
<b>Warranty</b>	3 years		
<b>Options</b>	n/a	<ul style="list-style-type: none"> <li>Cushman Truck Carriage Mounting Kit for WideSpin 1550 (#85824 or #85825) to a Carriage (#86184), includes hoses &amp; wiring for Cushman Truck (#86190)</li> <li>Toro or John Deere Truck Carriage Mounting Kit for WideSpin 1550 (#85824 or #85825) to a Carriage (#86184), includes hoses &amp; wiring for Toro or John Deere Trucks (#86191)</li> <li>Tractor Carriage Mounting Kit for WideSpin 1550 (#85824 or #85825) to a Carriage (#86184), includes hoses &amp; wiring for tractors (#86192)</li> </ul>	<ul style="list-style-type: none"> <li>Mounting Kit to Toro Workman HDX and 2002 or later Toro Workman Trucks equipped with the Toro High Flow Hydraulic Kit (#86188)</li> <li>Mounting Kit to John Deere ProGator Truck equipped with John Deere Hydraulic Auxiliary Kit (#86189)</li> </ul>

Specifications subject to change without notice.

