



CR-20 Large Area Topdresser & Material Handler

Specifications

Model	#85444
Drive	Tractor's hydraulic system powers main belt, side conveyor, and spinners
Hopper Capacity	5 cubic yards (3.82 cubic meters)
Hopper	Galvanized steel panels
Transport Speed	Up to 15 MPH (24 km/h) empty; Up to 8 MPH (12.8 km/h) loaded
Topdressing Speed	Up to 6 MPH (9.6 km/h)
Conveyor Belt	32" (0.81 m) wide, pebble grain surface with heavy-duty polyester cord
Metering Gate	Manual adjustment for spinner gate, electronic adjustment for side conveyor gate
Smart Control	3-position switch; 9 programmable presets for both spinner and side conveyor; onboard rate calculator; instantaneous belt, spinner and side conveyor speed control; Joystick for side conveyor up/down, left/right; Rocker switches for adjusting side conveyor gate and deflector
Wheels & Tires	Four 33/16x 16.1, 10-ply turf tires
Hitch	Heavy-duty, adjustable height pin hitch
Tractor Requirements	Minimum of 45 HP (33.1 kW), 10 GPM hydraulic flow
Empty Weight	3,876 lbs (1,759 kg)
Dimensions	202" (5.13 m) long x 91" (2.53 m) wide x 95" (2.64 m) high
Optional Equipment	None
Warranty	1 Year, including Smart Controller

Distributed by:



www.centaur-asiapacific.com
info@centaur-asiapacific.com

*Hong Kong, Macau and Singapore