



CR-8 Topdresser and Material Handler

Specifications

Model	85473
Drive	Tractor's hydraulic system powers belt and attachments
Hopper Capacity	2.0 yd ³ (1.54 m ³)
Hopper	Galvanized steel
Spreading Width	12' to 40' (3.6 m to 12.0 m)
Transport Speed	Up to 8 MPH (12.8 km/h)
Topdressing Speed	Up to 8 MPH (12.8 km/h)
Conveyor Belt	18" (0.46 m) wide, pebble grain surface with heavy-duty polyester cord, single seam
Metering Gate	Full manual adjustment with curved gate
Controls	Patented 3-position switch with belt and spinner control and manually adjusted hydraulic speeds
Wheels & Tires	Four 26.5 x 14-12 4-ply turf tires with walking high beam suspension
Hitch	Heavy-duty pin hitch
Tractor Requirements	Minimum of 30 HP (22.4 kW) with one bank of hydraulics and 6 GPM flow
Empty Weight	1,421 lb (644 kg)
Dimensions	144" (3.6 m) long x 75" (1.9 m) wide x 67" (1.7 m) tall
Optional Attachments	Material handler conveyor with swivel (#86181)
Warranty	3 years

Distributed by:



www.centaur-asiapacific.com
info@centaur-asiapacific.com

*Hong Kong, Macau and Singapore