



Mete-R-Matic® IV Topdresser

Specifications

Model	85424
Drive	Wheels are driven by the ground; all six tires mechanically drive the conveyor and brush; no engine; no hydraulic system
Hopper Capacity	1 yd3 (0.76 m3)
Hopper Size	Top: 73 ½" x 39 3/8" (1.87 m x 1.00 m), Bottom: 60" x 20" (1.5 m x 0.51 m), Depth: 19" (0.48 m)
Spreading Width	60" (1.5 m)
Topdressing Speed	Up to 8 MPH (12.8 km/h)
Transport Speed	Empty: up to 15 MPH (24 km/h), Loaded: up to 8 MPH (12.8 km/h)
Application	From very fine to ¼" (6.5 mm)
Conveyor Belt	Wide rubber composition with patented, Chevron belt 60" (1.5 m)
Metering Gate	Taintor gate design is easily adjusted and provides a uniform opening up to 2 ¼" (57 mm)
Brush	9" (228 mm) diameter, polypropylene bristle
Controls	Electric clutch actuator to engage conveyor and brush. Metering gate control for depth of application.
Clutch	The main clutch is a mechanical ratchet design actuated electrically from the operator's position on the tow vehicle.
Wheels & Tires	Six, 16" x 6.50" x 8" rib tread turf tires
Hitch	Heavy-duty pin hitch
Empty Weight	882 lb (400 kg)
Warranty	3 Years

Distributed by:



www.centaur-asiapacific.com
info@centaur-asiapacific.com

*Hong Kong, Macau and Singapore