



Mete-R-Matic® XL Topdresser

Specifications

Model	85460
Drive	Wheels are driven by the ground; all tires mechanically drive the conveyor and brush; no engine; no hydraulic system
Hopper Capacity	60.75 ft ³ (1.72 m ³ ; 2.25 yd ³), galvanized panels
Hopper Size	Top: 79" x 65" (2.0 m x 1.7 m), Bottom: 60" x 46" (1.5 m x 1.17 m), Depth: 19" (0.48 m)
Payload	6,000 lb (2,721 kg)
Spreading Width	60" (1.5 m)
Topdressing Speed	Up to 8 MPH (12.8 km/h)
Transport Speed	Up to 8 MPH (12.8 km/h)
Conveyor Belt	Wide rubber composition with patented Chevron belt 60" (1.5 m)
Metering Gate	Taintor gate design is easily adjusted and provides a uniform opening up to 2 ¼" (57 mm)
Brush	9" (228 mm) diameter, polypropylene bristle
Controls	Electrically operated clutch for conveyor and brush drive. Metering gate adjusted by hand.
Clutch	The main clutch is a mechanical ratchet design actuated electrically from the operator's position on the tow vehicle
Wheels & Tires	Two, 33" x 15.50" – 16.5" flotation tires
Hitch	Adjustable height clevis 1" pin hitch
Tractor Requirements	Minimum of 30 HP (22.4 kW)
Empty Weight	2,110 lb (957 kg)
Electrical Requirements	12 volt DC, negative ground (electrical power provided by tow vehicle)

Distributed by:



*Hong Kong, Macau and Singapore

www.centaur-asiapacific.com
info@centaur-asiapacific.com