



Turfco TriWave™ 60 Overseeder

Specifications

Tractor Requirements	35 HP minimum to 60 HP maximum (26.1 kW to 44.7 kW)
Drive	540 PTO (tractor)
Hitch	Category 1 or 2, 3-pt. hitch
Weight	1,150 lb (521.6 kg) when hopper is empty
Maximum Weight with Full Hopper	Approximately 1,250 lb (567 kg)
Model	85851
Width	74" (1.88 m)
Height	51" (1.3 m)
Length	40" (1.02 m) without PTO shaft
Capacity	4.77 ft ³ (8,251 in ³)
Seed Application Pattern	Spacing 1 1/2" (38.1 mm) apart
Seeding Width	60" (1.52 m)
Seed Gate	Manually operated, variable opening
Warranty	3 years
Ground Speed	Up to 5.5 mph (8.85 km/h)
Optional Equipment	TriWave 3-Point Extension Kit
Productivity	Up to 3 acres per hour
Cutting Heads	3 heads, independently floating
Blade Assembly	3 WaveBlade sets, 30 total blades
Blade Assembly Operating Depth Range	0 to 1-3/8" (0 to 34.9 mm)

Distributed by:



*Hong Kong, Macau and Singapore

www.centaur-asiapacific.com
info@centaur-asiapacific.com